

Category 5e FTP Horizontal Cables Cable, 24AWG×4P,PE

STANDARD COMPLIANCES

All Category 5e Requirements as Per ANSI/TIA, ISO/IEC, and CENELEC EN Standards

ANSI/TIA-568-C.2 Cat.5e

ISO/IEC 2nd Edition 11801 Class D

CENELEC EN 50173-1

IEC 61156-5, CENELEC 2nd Edition EN 50288-2-1 for horizontal cable

Flame retardancy is tested according to UL1581

We Implemented RoHS Compliance for the Requirement of European Union Issued Directive 2002/95/EC.

CONSTRUCTION & CHARACTERISTICS

Conductor	Material / Size	Bare Copper / 24AWG
Insulation	Material	Foam-Skin PE
	Thickness	Nominal: 0.269 mm
	Diameter	Nominal: 1.055 mm
	Colors	Blue/White-Blue Orange/White-Orange Green/White-Green Brown/White-Brown
	Unaged Elongation	Min. 100%
	Unaged Tensile Strength	Min. 0.816 Kgf/mm ²
Screen	Material	Aluminum-Mylar tape
Drain Wire	Material	Tinned copper
Jacket	Material	LDPE
	Thickness	Nominal: 0.5 mm
	Diameter	Nominal: 6.0 mm
	Color	Black
	Unaged Elongation	Min. 350%
	Unaged Tensile Strength	Min. 0.989 Kgf/mm ²
Marking	ÔPÙ CAT.5E FTP (OUTDOOR USE) 24AWGX4P INSTALLATION CONFORM TO ANSI/TIA-568-C.2 & ISO/IEC 11801 ED.2 & EN 50288-2-1 & IEC 60332-1-2 [XXXXXXXXM]	

APPLICATIONS

1000BASE-T Gigabit Ethernet

10BASE-T, 100BASE-TX Fast Ethernet (IEEE 802.3)

100 VG - AnyLAN(IEEE802.12), 155/622 Mbps ATM

550MHz Broadband Video

Voice, T1, ISDN

ELECTRICAL PERFORMANCES

Dielectric Strength of Insulation	1200 V dc / 2 seconds			
Insulation Resistance Test	Min. 5000 MΩ·Km			
Conductor Resistance	Max. 9.38 Ω/100m at 20°C			
Resistance Unbalance	Max. 2%			
Capacitance Unbalance	Max. 160 pF/100m			
Mutual Capacitance	Max. 5600 pF/100m			
Impedance	772kHz	102Ω ± 15%		
	1~125MHz	100Ω ± 15%		
Attenuation & Near End Cross Talk	Frequency (MHz)	Max.Attenuation (dB/100 meters)	NEXT (dB), Min.	PSNEXT (dB), Min.
	1 MHz	2.0*	65.3*	62.3*
	4 MHz	4.1*	56.3*	53.3*
	8 MHz	5.8*	51.8*	48.8*
	10 MHz	6.5*	50.3*	47.3*
	16 MHz	8.2*	47.2*	44.2*
	20 MHz	9.3*	45.8*	42.8*
	25 MHz	10.4*	44.3*	41.3*
	31.25 MHz	11.7*	42.9*	39.9*
	62.5 MHz	17.0*	38.4*	35.4*
	100 MHz	22.0*	35.3*	32.3*
	125 MHz	24.9*	33.8*	30.8*

The asterisked (*) value are for information only. The minimum Next coupling loss for any pair combination at room temperature is to be greater than the value determined using the formula:

$$NEXT(f\text{ MHz}) \geq NEXT(0.772) - 15\text{LOG}_{10}(f\text{ MHz}/0.772)\text{dB}$$

CONFIGURATION

orange 2	green 3
white/orange	white/green
blue 1	brown 4
white/blue	white/brown

